

MOTORTEC

CATÁLOGO

2024



ACEITES 100% SINTÉTICOS

WWW.MOTORTECLUBRICANTS.COM



RESISTENCIA Y DURABILIDAD

Sr. No.	Test Parameter	Specification Requirement	Method	Result
1	Color	--	Visual	RED
2	Appearance	Clear bright Liquid	Visual	Clear bright Liquid
3	Density at 29.5°C	To be Report	ASTM D1298	0.862
4	Kinematic Viscosity @ 40°C	To be Report	D 445	172
5	Kinematic Viscosity @ 100°C	To be Report	D 445	20.5
6	Viscosity index	125 min.	D 2270	140
7	Flash point °C	230 Min.	D 92	240
8	Pour Point °C	-21 MIN	D 97	-21



**DETALLES
DEL ACEITE**



10W40

Sr. No.	Test Parameter	Specification Requirement	Method	Result
1	Color	--	Visual	RED
2	Appearance	Clear bright Liquid	Visual	Clear bright Liquid
3	Density at 29.5°C, K/I	To be Report	ASTM D1298	0.868
4	Kinematic Viscosity @ 40°C, Cst.	To be Report	D 445	100.5
5	Kinematic Viscosity @ 100°C, Cst.	To be Report	D 445	14.6
6	Viscosity index	125 min.	D 2270	150
7	Flash point °C	230 Min.	D 92	240
8	Pour Point °C	-21 MIN	D 97	-35